

Options and Accessories



Lighting Package*



Plastic Canopy Top



Custom Van Box



Rear Cargo Cage



Electric Bed Lift




Underhood Storage
(Gas Only)



Stake-Side Kit



2-Inch Front
Receiver Hitch



Cargo Bed Toolbox



2,500 lb Warn Winch



Pintle Hitch



Cab Heater
(Gas Only)



Nerf Bars



54- or 62-Inch
Plow Blade



Swisher Trailmower



Swisher Dump Cart



50-Gallon Sprayer

*Includes horn, turn signals and brakelights

Club Car

CARRYALL 295

UTILITY VEHICLE



Ingersoll Rand is a world leader in the field of compact vehicles and equipment. Our widely known Bobcat® brand includes an extensive line of powerful, nimble compact construction equipment and attachments, and our state-of-the-art engineering capabilities and stylish designs are reflected in our world famous Club Car® vehicles.

1.800.ClubCar • +1 706.863.3000

www.clubcar.com www.bobcat.com www.ingersollrand.com

CCN 18033076 Rev 08/06



CARRYALL 295

Look no further for the industry's first fully automatic 4x4 utility vehicle. Club Car's revolutionary IntelliTrak™ 4-wheel-drive system constantly senses the driving environment and instantly engages and disengages 4-wheel-drive operation as the surroundings change. With nothing to engage, shift or lock, you get a 4x4 that's easy for your whole team to drive. With unique comfort features and durable construction, the Carryall 295 means serious business anywhere you put it to work.

Features

IntelliTrak™:
An automatic full-time,
All-Wheel-Drive system



20 hp air-cooled Honda®
gas or 20 hp liquid-cooled
Kubota® diesel engine



Standard Color:
Dark Gray



Optional Color:
Green



Roll Over Protective
Structure certified
to meet 5 different
international
standards



Rustproof, non-corrosive,
box tube 6061 aircraft-grade
aluminum frame, chassis
and cargo box



15.1 ft³ (0.4 m³)
Cargo Box carries
800 lb (362.9 kg)



4-wheel,
hydraulic
disc brakes



Double A-Arm
front suspension
w/coil-over shocks

Additional Features

- Maximum speed of 25 mph (40.2 kph)
- 1,200 lb (544.3 kg) total vehicle capacity; heavy-duty 1,450 lb (657.7 kg)
- Maximum hp @ 3,600 rpm exceeds SAE J1940 Performance Standards
- 12.1 in (30.7 cm) ground clearance under foot platform to handle rough terrain
- 25" heavy-duty, all-terrain tire standard; 25" heavy-duty, mud tire optional

Specifications

	<i>Carryall 295 Gasoline</i>	<i>Carryall 295 Diesel</i>	
POWER SUPPLY	Engine	Honda GX620, 614 cc, 2-cylinder	Kubota D722, 719 cc, 3-cylinder
	Engine – Cooling	Air	Liquid
	Engine – Lubrication & Oil Filter Type	Full-pressure spin-on	Full-pressure spin-on
	Max Torque	32.5 ft-lb (44.1 Nm)	33 ft-lb (44.7 Nm)
	Horsepower	20 (14.9 kw)	20 (14.9 kw)
	Ignition	Transistorized magneto	Compression
	4WD Engagement	Automatic – IntelliTrak	Automatic – IntelliTrak
	Differential – Front	Automatic – IntelliTrak	Automatic – IntelliTrak
	Differential – Rear	Auto locking – IntelliTrak	Auto locking – IntelliTrak
	Electrical System	12-volt, 500 CCA	12-volt, 500 CCA
Torque Converter	CVT	CVT	
STEERING/ SUSPENSION	Steering Type	Rack & pinion	Rack & pinion
	Tilt Steering Wheel	Standard	Standard
	Adjustable Driver's Seat	Only available with bucket seat option	Only available with bucket seat option
	Suspension – Front	Independent double A-arms w/coil-over shocks	Independent double A-arms w/coil-over shocks
	Suspension – Rear	Swing arm w/coil-over shocks	Swing arm w/coil-over shocks
	Brakes	4-wheel, hydraulic disc	4-wheel, hydraulic disc
	Park Brake	Automotive style	Automotive style
FRAME/CHASSIS	Frame/Chassis	Tubular aluminum	Tubular aluminum
	Body – Front	GE Geloy High-impact, scratch-resistant, injection molded color	GE Geloy High-impact, scratch-resistant, injection molded color
	Body – Rear	All aluminum cargo bed	All aluminum cargo bed
	Tires – Front	All-terrain, 25 x 10.5-12, 4-ply, (mud tires optional)	All-terrain, 25 x 10.5-12, 4-ply, (mud tires optional)
	Tires – Rear	All-terrain, 25 x 10.5-12, 4-ply, (mud tires optional)	All-terrain, 25 x 10.5-12, 4-ply, (mud tires optional)
	Instrumentation	Electronic fuel gauge/hour meter, low oil warning light (speedometer optional)	Electronic fuel gauge/hour meter, low oil warning light, coolant high temp warning light (speedometer optional)
DIMENSIONS	Bed Length x Width x Height	48.8 x 49.8 x 10.9 in (124 x 126.5 x 27.7 cm)	48.8 x 49.8 x 10.9 in (124 x 126.5 x 27.7 cm)
	Overall Bed Height	33 in (83.8 cm)	33 in (83.8 cm)
	Bed Load Capacity	800 lb (362.9 kg)*	800 lb (362.9 kg)*
	Total Vehicle Capacity	1,200 lb (544.3 kg)**	1,200 lb (544.3 kg)**
	Fuel Tank Capacity	6.5 gal (24.6 L)	6.5 gal (24.6 L)
	Overall Length x Width x Height	124.6 x 60 x 78.6 in (316.5 x 152.4 x 199.6 cm)	124.6 x 60 x 78.6 in (316.5 x 152.4 x 199.6 cm)
	Wheelbase	88.7 in (225.3 cm)	88.7 in (225.3 cm)
	Ground Clearance – Differential	7.4 in (18.8 cm)	7.4 in (18.8 cm)
	Tread Centers (Front/Rear)	48.8 in (124 cm) front and rear	48.8 in (124 cm) front and rear
	Dry Weight (Less Batteries)	1,339 lb (599 kg)	1,475 lb (669.1 kg)
	Maximum Speed	25 mph (40.2 kph)	25 mph (40.2 kph)
	Turning Radius	12.1 ft (3.7 m)	12.1 ft (3.7 m)
	Vehicle Warranty	2-year/2,000-hour, limited	2-year/2,000-hour, limited

*1,050 lb (476.3 kg) available
**1,450 lb (657.7 kg) available

